



SNOW MOBILE OIL SUPER SYN 2T

Product Description:

SNOW MOBILE OIL SUPER SYN 2T is a fully synthetic high performance lubricant developed for air & water cooled 2-stroke engines. The special formulation ensures excellent engine protection, cleanliness and low smoke, even under extreme operating conditions.

SNOW MOBILE OIL SUPER SYN 2T is based on a high quality fully synthetic base oils in combination with a special selected additive package to obtain the following properties:

- Outstanding protection against piston scuffing and premature wear of engine components.
- Excellent control against engine deposits, exhaust system blocking.
- Extended engine life without power loss.
- Low ash additive technology prevents pre-ignition and spark plug fouling.
- Specially selected synthetic base fluid reduces visible exhaust smoke.
- Easy miscibility with gasoline ensures stable homogeneous mixture even at very low ambient temperatures.
- Specially designed to meet the high performance demands of the BRP E-Tec engines.



SNOW MOBILE OIL SUPER SYN 2T exceeds the following performance criteria.:

**API TC
TISI**

**JASO FD
ROTAX 253**

**ISO-L-EGD
Husqvarna 272**

Suitable for use: E-Tec

Property	Unit	Test Method	Typical Value
Density@15°C	kg/m ³	ASTM D4052	868.8
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	36.53
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	7.54
Viscosity Index		ASTM D2270	178
Flash Point COC	°C	ASTM D92	>150
Pour Point	°C	ASTM D7346	-48
Total Base Number	mgKOH/g	ASTM D2896	1.9
Sulphated Ash	%Wt	ASTM D874	0.14

Product Nr: 42911
Date Superseded: -

Date Issued: 6-5-2026
Revision nr: -