MOTIP Backlight Paint

Technical Information



Markera baklyktorna på din bil med MOTIP Backlight Spray. Den transparenta lacken har en varaktig glans och är repfri och stöttålig. Lacken är resistent mot bensin, kemikalier och väder.

Beställningsnummer: 00260, 00261, 00160, 00161, 880112

Kvalitet & egenskaper

Ej lämplig för behandling av ytor av polykarbonat!
Varaktig glans
Repfri och stötsäker
Beständig mot bensin, kemikalier och väderpåverkan
God vidhäftning

Fysikaliska och kemiska data

Bas: Alkydharts
Kolourname:
- black
- red
- orange

Lukt: Kännetecken
Grad av glans: glans, >75
Effektivitet:
- 400 ML – 8 backlights
- 150 ML – 2 to 4 backlights

Dammtorr: 10 - 20 min
Torr vid beröring: 60 min
Helt torr: 4 h
Överdragbar: 4 min
Ytor: Backlights
Minsta arbetstemperatur: 10 °C
Maximal arbetstemperatur: 25 °C
Lagringsstabilitet: 10 y
Innehållt:
- 400 ML
- 150 ML

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim – info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega – info-nl@european-aerosols.com

Hur man använder

Läs anvisningarna på förpackningen noggrant före användning och följ dessa.
Ytan måste vara ren, torr och fri från fett.
Burken ska ha rumstemperatur. Bästa temperatur för behandling 10–25 °C.
Skaka burken i 2 minuter före användning och provspraya på en liten yta. Håll burken cirka 25–30 centimeter från ytan som ska behandlas.
Spraya lacken i flera tunna lager, tills önskat resultat har uppnåtts. (Skaka burken igen innan du applicerar nästa lager.)
Rengör ventilen efter användning (vänd burken upp–och-ned och tryck på munstycket i cirka 5 sekunder).
Torktiden beror på omgivningstemperatur, luftfuktighet och det applicerade lacklagrets tjocklek.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as “special refuse”.

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of March 31, 2026 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim – info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega – info-nl@european-aerosols.com